





These ultra slim profile can-less recessed LED downlights are designed for easy installation into new construction or remodel applications. Tunable white luminaires include an integral Selectable CCT switch located on the junction box of each luminaire with a quick connect that allows for easy disconnect and mounting in the ceiling.

FEATURES

- · 120VAC 700lm / 10W or 1000lm / 12W
- · Field selectable CCT: 2700K / 3000K / 3500K / 4000K / 5000K
- · 90+CRI
- · Triac dimming
- · No housing required and includes pre-wired junction box
- · Junction box includes tunable color temperature switch
- · Quick disconnect allows for easy installation
- · IC Air-tight rated
- · Suitable for Wet locations
- · Energy Star listed, CEC Title 24 JA8 listed, ETL approved, RoHS compliant













LS-CS-4-5CCT-RND 4" Round



LS-CS-6-5CCT-RND 6" Round



LS-CS-4-5CCT-SQ 4" Square



LS-CS-6-5CCT-SQ 6" Square







Catalog Number	Size	Voltage	Wattage	Efficacy	Lumen	ССТ	CRI	Life Time
LS-CS-4-5CCT-RND	4"	120VAC	10W	75lm/W	700lm	27K/30K/35K/40K/50K	90+	50,000Hrs.
LS-CS-4-5CCT-SQ	4"	120ACV	10W	75lm/W	700lm	27K/30K/35K/40K/50K	90+	50,000Hrs.
LS-CS-6-5CCT-RND	6"	120ACV	12W	85lm/W	1000lm	27K/30K/35K/40K/50K	90+	50,000Hrs.
LS-CS-6-5CCT-SQ	6"	120ACV	12W	85lm/W	1000lm	27K/30K/35K/40K/50K	90+	50,000Hrs.