



4" & 6" Wattage & CCT Selectable LED Retrofit



High Quality, Design and Energy Efficient



Wattage & CCT Switch



4" & 6" Wattage tuning and CCT selectable Retrofit series include two tunable switches; Selectable Lumens allows the end user to determine the wattage input and Selectable CCT allows for changing the color temperature appearance. Spun aluminum construction provides clean sharp edges and is suitable for use with most 4" & 6" recessed housings. Deep regressed optics and round aperture deliver even and glare-free illumination.



LSRL-4WT5CCTSWH
4" Smooth, White finish



LSRL-6WT5CCTSWH
6" Smooth, White finish

FEATURES

- 4" Retrofit: 500lm/4W; 700lm/10W; 850lm/12W
6" Retrofit: 850lm/12W; 1100lm/15W; 1260lm/18W
- Selectable CCT: 2700K, 3000K, 3500K, 4000K, 5000K @ 90+CRI
- Baffle or Smooth reflector
- Includes medium base socket adapter for easy retrofitting in 4" & 6" recessed housings
- Certified to the high efficacy requirements of California JA8 Title 24
- cETLus listed
- ENERGY STAR Certified



LSRL-4WT5CCTBBL
4" Baffle, Black finish



LSRL-6WT5CCTBBL
6" Baffle, Black finish



Catalog Number	Size	Type/Finish	Selectable Lumen/Wattage	Selectable CCT	CRI	Certified
LSRL-4WT5CCT	4"	B -Baffle	500lm/4W; 700lm/10W; 850lm/12W	27K/30K/35K/40K/50K	90+	cETLus
		S -Smooth				
LSRL-6WT5CCT	6"	B -Baffle	850lm/12W; 1100lm/15W; 1260lm/18W	27K/30K/35K/40K/50K	90+	cETLus
		S -Smooth				