



LS-2-207-5CCT

2" Selectable 5CCT Round Adjustable Gimbal LED Retrofit Downlight

LUMENS: 800LM

COLOR TEMPERATURE: 27K/30K/35K/40K/50K

APERTURE: Round

Description 2" LED adjustable gimbal retrofit downlight include a 5CCT selectable switch allows for changing the color temperature appearance to suite the environment mood. It is compatible for use with most 2" recessed housings. The retrofit kit comes with a E26 medium screw-base Edison adapter for easy installation into standard incandescent sockets.



Selectable 5 CCT Switch



FEATURES


- Selectable 5CCT (27K/30K/35K/40K/50K)
- Wattage 8W
- Light Output: 27K-770lm, 30K-800lm
35K-840lm, 40K-850lm, 50K-820lm
- 90+ CRI
- 120-277V
- Adjustable 27° tilt Gimbal
- Dimmable to 10% with most standard Triac dimmers
- 50,000 Hours Life
- 5 Year Limited Warranty
- cUL classified for Wet Locations



PRODUCT IMAGES & DIMENSIONS



LS-2-207-5CCT
(Adjustable Gimbal)



SPECIFICATIONS

PART NUMBER	SIZE	TYPE	LUMEN/WATTAGE	SELECTABLE 5CCT	VOLTAGE	DIMMING	CRI	FINISH	LISTING
LS-2-207-5CCT	2"	Adj. Gimbal	800lm/8W	27K/30K/35K/40K/50K	120-277V	Yes	90+	White	cULus