

Patented LED Alabaster Flush Mount



Key Features

- Spanish Alabaster with DIY Decorative trim. (Customized trims are available)
- 2700K/3000K/3500K/4000K/5000K CCT Selectable.
- Easy Installation by twist-and-lock brackets.


7" | 9" | 12"



ELECTRICAL

VOLTAGE	AC120V AC 60HZ
POWER FACTOR	≥0.9
DIMMABLE	TRIAC DIMMING
SURGE PROTECTION	0.5KV
Flicker	<30%

DIMENSION



DIMENSION	A (Diameter)	B (Height)
7"	7.15"	1.06"
9"	8.94"	1.06"
12"	11.87"	1.06"

PERFORMANCE

WARRANTY	5 YEAR
CERTIFICATIONS	FCC, ETL, ROHS, JA8&T24
RATE LIFE	>50,000 HOURS
OPERATING TEMPERATURE	-10°C TO + 45°C
CCT	2700K/3000K/3500K/4000K/5000K
SDCM	≤ 6
CRI	RA90
R9	> 0
BEAM ANGLE	120°
Environment	Damp Location
FIRE RATING	V0
HOUSING	Alabaster+Metal+White PC(RAL9003)

ENERGY CHART

MODEL NO	SIZE inches	WATTAGE	EFFICIENCY lm/w	DELIVERED LUMENS	CCT
P617-K129-X120B5T-W1 C33-7MB	7"	12W	40LM/W±5%	480LM±5%	2700K 3000K 3500K 4000K 5000K
P617-K129-X120B5T-W1 C33-7GD	7"	12W	40LM/W±5%	480LM±5%	
P619-K189-X120B5T-W1 C33-9MB	9"	18W	53LM/W±5%	950LM±5%	
P619-K189-X120B5T-W1 C33-9GD	9"	18W	53LM/W±5%	950LM±5%	
P6112-K249-X120B5T-W1 C33-12MB	12"	24W	58LM/W±5%	1400LM±5%	
P6112-K249-X120B5T-W1 C33-12GD	12"	24W	58LM/W±5%	1400LM±5%	

RECOMMENDED DIMMERS

LUTRON			LEVITON	
DVCL-153P-WH	DVELV-300P-WH	S-600P-WH	6674	6615-POW
DVSCCL-153P-ES	PD-6WCL, Caseta Wireless dimmer	SELV-300P-IV	6633	RHCL453PW
DVCL-253P-WH	CTCL-153P-IV	AYCL-253P-WH	TSLO6-1LW	