

LS-EL

Edge-Lit Single Face LED Exit Sign



LS-EL-GRAY-G LS-EL-GRAY-R

Description Thermoplastic, compact, low profile LED compact Exit sign with battery back-up is great for commercial and industrial applications requiring a reliable, bright and energy efficient life safety solution. It can be wall, side or ceiling mounted.

FEATURES


- · Energy efficient LED compact and decorative design
- · Removable directional indicator arrows
- · 6" height with 3/4" stroke and chevron directional arrows
- · Single face with clear background
- · 120/277V dual voltage operation
- · 90 minutes emergency operation
- · Injection-molded thermoplastic housing
- · Available in Gray, Silver or White housing
- · 5 years warranty on all electronics and housing
- · cULus Listed for Damp Location

Mounting Wall, side or ceiling. Universal knockouts on back plate allow for wall mounting directly to standard J-Box. Canopy and mounting hardware provided.

Lamps 2W LED at 120V & 277V. LED lamps are operating in normal (AC input) and Emergency (DC input) modes. LEDs have a minimum rated lamp life of 100,000 hours.

Battery 3.6V long-life maintenance-free and rechargeable Ni-Cad battery. LVD (Low Voltage Disconnection) prevents battery from deep discharge.






PRODUCT IMAGES & DIMENSIONS



LS-EL-GEdge-Lit LED Exit Sign,
Green Letters, Silver Housing



LS-EL-REdge-Lit LED Exit Sign,
Red Letters, Silver Housing





SPECIFICATIONS

PART NUMBER	WATTAGE	VOLTAGE	EMERGENCY DURATION	LETTER COLOR	HOUSING FINISH	LISTING
LS-EL-G	2W	120/277V	90 Minutes	Green	Silver	cULus
LS-EL-R	2W	120/277V	90 Minutes	Red	Silver	cULus
LS-EL-G-WHITE	2W	120/277V	90 Minutes	Green	White	cULus
LS-EL-R-WHITE	2W	120/277V	90 Minutes	Red	White	cULus
LS-EL-GRAY-G	2W	120/277V	90 Minutes	Green	Gray	cULus
LS-EL-GRAY-R	2W	120/277V	90 Minutes	Red	Gray	cULus