



LS2-CS-3G

3" Canless Dedicated CCT Adjustable Round Gimbal LED Recessed Downlight

LUMENS: 580lm

COLOR TEMPERATURE: 30K/40K/50K

APERTURE: Round

Description 3" adjustable round gimbal LED recessed downlight included junction box which can be install directly in insulated ceiling without any thermal housing. Fixture is compatible with industry standard forward-phase / reverse-phase and TRIAC/ELV dimmers.

FEATURES

- No housing is required - easy and fast installation
- 580lm / 7W
- Dedicated 3000K, 4000K and 5000K
- 90+CRI
- 38° beam angle and 30° tilt
- IC rated
- 120V Triac dimming
- Available in Black or White finish
- 5 years warranty
- cETLus Listed for Damp Locations

Mounting Plate Available
(Sold Separately)



LS-CS-3R-MP
3" Round Mounting Plate




PRODUCT IMAGES & DIMENSIONS



LS2-CS-3G

3" Canless Adjustable Round Gimbal
White Finish



LS2-CS-3G-BL

3" Canless Adjustable Round Gimbal
Black Finish

SPECIFICATIONS

PART NUMBER	SIZE	APERTURE	LUMEN/WATTAGE	DEDICATED CCT	CRI	VOLTAGE	DIMMING	FINISH	LISTING
LS2-CS-3G-3K	3"	Round Adjustable Gimbal	580lm/7W	3000K	90	120V	TRIAC	White	cETLus
LS2-CS-3G-4K	3"	Round Adjustable Gimbal	580lm/7W	4000K	90	120V	TRIAC	White	cETLus
LS2-CS-3G-5K	3"	Round Adjustable Gimbal	580lm/7W	5000K	90	120V	TRIAC	White	cETLus
LS2-CS-3G-3K-BL	3"	Round Adjustable Gimbal	580lm/7W	3000K	90	120V	TRIAC	Black	cETLus
LS2-CS-3G-4K-BL	3"	Round Adjustable Gimbal	580lm/7W	4000K	90	120V	TRIAC	Black	cETLus
LS2-CS-3G-5K-BL	3"	Round Adjustable Gimbal	580lm/7W	5000K	90	120V	TRIAC	Black	cETLus