

# LIGHTING SPOT<sub>26</sub>

## 4 inch Slope LED Retrofit

4" Round Smooth & Baffle Slope LED Downlight Retrofit Kit



Use the switch to set the desired CCT (Correlated Color Temperature).



Smooth Slope LED Downlight



Baffle Slope LED Downlight

### - Finishes



B - Black



BZ - Bronze

### Selectable 3 CCT Switch



### Selectable 5 CCT Switch



## SPECIFICATION

### QUICK FEATURES

- Diecast aluminum heatsink dissipates heat from the LED board
- 4 different colors : **W**-White / **B**-Black / **SN**-Satin Nickel / **BZ**-Bronze
- 3 or 5 Position CCT Selectable switch (2700K / 3000K / 3500K / 4000K / 5000K)
- Dimmable to 10% with most standard triac or 0-10V dimmers
- E26 medium screw-base Edison adaptor provides easy installation into Incandescent housings (GU10 and GU24 socket adaptor available - sold separately)
- cUL classified
- Damp Location
- Lifetime of 50,000 hours
- 5 year warranty

### PERFORMANCE DATA

Input Voltage	120V (Triac Dimming Ver.)	120-277V (0-10V Dimming Ver.)
Frequency	50 / 60Hz	
T Ambient	-30 °C ~ 40 °C (-22 °F ~ 104 °F)	

(all values at 25°C without a dimming control in circuit)

### LIGHT SOURCE TEST TABLE

Wattage	2700K	3000K	3500K	4000K	5000K
12 W	800 lm	820 lm	830 lm	850 lm	870 lm



CRI 90

### DIMENSIONONS




Triac Dimming Ver.

MODEL NO.  
SLKT400  
SLKT403




Triac Dimming Ver.

MODEL NO.  
SLKT400-3CCT  
SLKT403-3CCT



Triac Dimming Ver.

MODEL NO.  
SLKT400-5CCT  
SLKT403-5CCT



0-10V Dimming Ver.

MODEL NO.  
SLKT400-5CCT-M  
SLKT403-5CCT-M

