

4"/6" LED 5CCT DOWNLIGHT


0-10V Dimming

Features


- Conduit quick-connect connectors facilitate installation.
- Protected LED driver performs at 120-277V.
- 0-10V dimming at 120-277V.
- Available in 5 CCT 2700K, 3000K, 3500K, 4000K and 5000K.
- cULus classified.
- Energy star qualified.
- Wet locations (Not suitable for coastal/salt water area).
- Damp locations.
- RoHS compliances.
- Title 24 compliant.
- Tested in accordance with IESNA LM79 & LM80.




Dimension



LSL-400EN-5CCT



LSL-403EN-5CCT



LSL-644EN/SQ-5CCT

Specification

Catalog Number	Size	Input Voltage (V)	Lamp Watt (W)	Efficacy (Lumen/watt)	Lumen Output (lm)	CCT (K)	CRI	Life Time (Hrs)
LSL-400EN-5CCT	4FT	120-277VAC	10	67-72	670-720	27/30/35/40/50	90	50000
LSL-403EN-5CCT	4FT	120-277VAC	10	67-72	670-720	27/30/35/40/50	90	50000
LSL-644EN/SQ-5CCT	6FT	120-277VAC	14	70-78	980-1100	27/30/35/40/50	90	50000