



LS-LV4-5CCT

4" 12V Low Voltage 5CCT Retrofit Downlight

LUMENS: 750lm

COLOR TEMPERATURE: Selectable 5CCT

APERTURE: Round Adjustable



CCT SWITCH



Description 4" Low Voltage Retrofit features an integral tunable CCT switch to change the color temperature appearance. Spun aluminum body provides clean sharp edges with deep regressed round aperture deliver anti-glare illumination. It's an economical solution to convert existing, new construction or remodel low voltage recessed housings into LED luminaire.

FEATURES

- 12V Low Voltage
- 750lm / 10W
- Selectable CCT: 2700K, 3000K, 3500K, 4000K, 5000K @ 90+CRI
- Baffle or Smooth Reflector option in Black or White finishes
- Compatible with 4" IC & Non-IC Recessed Low Voltage Housings
- Dimmable
- cETLus listed

PRODUCT IMAGES & DIMENSIONS



LS-LV4-5CCT-BF-BL
4" 12V 5CCT Baffle, Black





LS-LV4-5CCT-BF-WH
4" 12V 5CCT Baffle, White



LS-LV4-5CCT-SM-BL
4" 12V 5CCT Smooth, Black



LS-LV4-5CCT-SM-WH
4" 12V 5CCT Smooth, White



SPECIFICATIONS

Catalog Number	Size	Voltage	Wattage	Lumen	CCT	Reflector Type	Finish	Certificated
LS-LV4-5CCT-BF-BL	4"	12V	10W	550lm	27K/30K/35K/40K/50K	Baffle	Black	cETLus
LS-LV4-5CCT-BF-WH	4"	12V	10W	750lm	27K/30K/35K/40K/50K	Baffle	White	cETLus
LS-LV4-5CCT-SM-BL	4"	12V	10W	550lm	27K/30K/35K/40K/50K	Smooth	Black	cETLus
LS-LV4-5CCT-SM-WH	4"	12V	10W	750lm	27K/30K/35K/40K/50K	Smooth	White	cETLus