4" Trimless Reflector For 4" Standard Housing



Catalog Number Project Name



Description

The LED module is made with die-cast, so it is appropriate for heat dissipation. LED Module is the form of replacement, so you can easily replace the LED module The body of the trim is made of light weight plastic 3 tension clips pre-installated on unit for easy installation LED module can be rotated 440 dregrees, and tilted 28 degrees Protected LED driver performs at 120V (120-277V available also) Dimming down to 10% with most dimmers at 120V only CCT 2700K, 3000K, 4000K and 5000K CRI 90 Long life LED chips guaranteed up to 50,000 Hours.

DELIVERED LUMENS	WATTAGE	EFFICACY
900 Lumens	9 watts	100 lumens/watts


ССТ	2700K, 3000K, 4000K, 5000K	VOLTAGE	120V (*120-227V)	TRIM OPTION	Trimless
CRI	CRI > 90	LIFE TIME	50,000 Hrs	FINISH	White
DIMMING	100%-10%, TRIAC	RATINGS	Energy Star, UL, T24	WARRANTY	5 years

^{*}Please consult factory


DIMENSIONS I LISTINGS

Adjustability






LS-MDC-4/27K LED Module LS-MDC-4/3K LS-MDC-4/4K LS-MDC-4/5K



LS-MD-4"RND Round MUD Ring



LS-MD-4"SQ Square MUD Ring











ORDERING

LS-MDC-4-27K-LS-MD-4-RND

SERIES	SIZE	ССТ	TRIMLESS OPTION
LS-MDC-4	4"	27K - 2700K 3K - 3000K 4K - 4000K 5K - 5000K	LS-MD-4-RND - Round LS-MD-4-SQ - Square

Compatible 4" LS Housings





LS-4INCH-R-IC-AT

LS-4INCH-R-IC-AT