

Introducing LED Tape Light

24V COB Up to 200LM/FT
Continuous Glow

Features

- COB Design, with more chips on PCB, more continuous glow.
- Up to 320 chips on 3 3/8FT PCB, only 1.89mm space between chips.
- Cuttable at every 328FT(24V) length.
- Efficiency up to 90Lm/W.
- CE, Rohs, UL listed.



Specification

Catalog Number	Size (mm)	Reel Length (FT)	Input Voltage (V)	Lamp Watt (W/FT)	Efficiency (LM/W)	Lumen Output (LM/FT)	CCT (K)	CRI	Life Time (HRS)	Max Run (FT)
LS-TPC2.5W/24V/5m/3K	8*3	16.4	24VDC	2.5	85	198	3000	>90	50,000	16
LS-TPC2.5W/24V/20m/3K	8*3	65.6	24VDC	2.5	85	198	3000	>90	50,000	16
LS-TPC2.5W/24V/5m/3K-R	10*5	16.4	24VDC	2.5	80	198	3000	>90	50,000	16
LS-TPC2.5W/24V/5m/4K	8*3	16.4	24VDC	2.5	90	213	4000	>90	50,000	16
LS-TPC2.5W/24V/20m/4K	8*3	65.6	24VDC	2.5	90	213	4000	>90	50,000	16
LS-TPC2.5W/24V/5m/4K-R	10*5	16.4	24VDC	2.5	85	198	4000	>90	50,000	16
LS-TPC2.5W/24V/5m/5K	8*3	16.4	24VDC	2.5	90	213	5000	>90	50,000	16
LS-TPC2.5W/24V/5m/5K-R	10*5	16.4	24VDC	2.5	85	198	5000	>90	50,000	16
LS-TPC/08	1 Terminal LED PCB Connector, suitable for 8mm width LED COB tape light.									
LS-TPC/X08	1 Terminal LED PCB Connector and a 7.87" red/black 22AWG wire, suitable for 8mm width LED COB tape light.									

**R= Suitable for outdoor.

