

Introducing LED Tape Light 24V COB Up to 400LM/FT Continuous Glow

Features

- COB Design, with more chips on PCB, more continuous glow.
- Up to 528 chips on 3 3/8FT PCB, only 1.89mm space between chips.
- Cuttable at every 328FT(24V) length.
- Efficiency up to 90Lm/W.
- CE, Rohs, UL listed.



Specification

| Catalog Number | Size (mm) | Reel Length (FT) | Input Voltage (V) | Lamp Watt (W/FT) | Efficiency (LM/W) | Lumen Output (LM/FT) | CCT (K) | CRI | Life Time (HRS) | Max Run (FT) |
|-------------------------|--|------------------|-------------------|------------------|-------------------|----------------------|---------|-----|-----------------|--------------|
| LS-TPC4.63W/24V/5m/27K | 10*3 | 16.4 | 24VDC | 4.63 | 80 | 366 | 2700 | >90 | 50,000 | 16 |
| LS-TPC4.63W/24V/5m/3K | 10*3 | 16.4 | 24VDC | 4.63 | 85 | 381 | 3000 | >90 | 50,000 | 16 |
| LS-TPC4.63W/24V/20m/3K | 10*3 | 65.6 | 24VDC | 4.63 | 85 | 381 | 3000 | >90 | 50,000 | 16 |
| LS-TPC4.63W/24V/5m/3K-R | 12*5 | 16.4 | 24VDC | 4.63 | 80 | 366 | 3000 | >90 | 50,000 | 16 |
| LS-TPC4.63W/24V/5m/4K | 10*3 | 16.4 | 24VDC | 4.63 | 90 | 396 | 4000 | >90 | 50,000 | 16 |
| LS-TPC4.63W/24V20m/4K | 10*3 | 65.6 | 24VDC | 4.63 | 90 | 396 | 4000 | >90 | 50,000 | 16 |
| LS-TPC4.63W/24V/5m/4K-R | 12*5 | 16.4 | 24VDC | 4.63 | 85 | 381 | 4000 | >90 | 50,000 | 16 |
| LS-TPC4.63W/24V/5m/5K | 10*3 | 16.4 | 24VDC | 4.63 | 90 | 396 | 5000 | >90 | 50,000 | 16 |
| LS-TPC4.63W/24V/5m/5K-R | 12*5 | 16.4 | 24VDC | 4.63 | 85 | 381 | 5000 | >90 | 50,000 | 16 |
| LS-TPC/10 | 1 Terminal LED PCB Connector, suitable for 10mm width LED COB tape light. | | | | | | | | | |
| LS-TPC/X10 | 1 Terminal LED PCB Connector and a 7.87" red/black 22AWG wire, suitable for 10mm width LED COB tape light. | | | | | | | | | |

**R= Suitable for outdoor.

