

# Introducing LED Tape Light 24V SMD Up to 800LM/FT

## Features

- New Wiring Design, 8 LED Per Cut, reaching higher efficiency compared to traditional 6 LED per Cut under the same watts.
- Using high quality 22-26lm/LED 2835 SMD as light source, reaching high efficiency.
- Although the max current of 2835 LED is 60mA, we running it @33mA, reaching the highest efficiency.



## Specification

Catalog Number	Size (mm)	Reel Length (FT)	Input Voltage (V)	Lamp Watt (W/FT)	Efficiency (LM/W)	Lumen Output (LM/FT)	CCT (K)	CRI	Life Time (HRS)	Max Run (FT)
LS-TPL7.5W/24V/5m/27K	10*3	16.4	24VDC	7.5	105	785	2700	>90	50,000	16
LS-TPL7.5W/24V/5m/3K	10*3	16.4	24VDC	7.5	110	820	3000	>90	50,000	16
LS-TPL7.5W/24V/20m/3/K	10*3	65.6	24VDC	7.5	110	820	3000	>90	50,000	16
LS-TPL7.5W/24V/5m/3K-R	12*5	16.4	24VDC	7.5	105	785	3000	>90	50,000	16
LS-TPL7.5W/24V/5m/4K	10*3	16.4	24VDC	7.5	115	855	4000	>90	50,000	16
LS-TPL7.5W/24V/20m/4K	10*3	65.6	24VDC	7.5	115	855	4000	>90	50,000	16
LS-TPL7.5W/24V/5m/4K-R	12*5	16.4	24VDC	7.5	105	785	4000	>90	50,000	16
LS-TPL7.5W/24V/5m/5K	10*3	16.4	24VDC	7.5	115	855	5000	>90	50,000	16
LS-TPL7.5W/24V/5m/5K-R	12*5	16.4	24VDC	7.5	105	785	5000	>90	50,000	16
LS-TPL/FC10m	1 Terminal New LED Fast Connector with a 5.91" length wire, suitable for 10mm width 70LEDs/FT 12VDC or 24VDC LED tape light.									

\*\*R= Suitable for outdoor.

