LED COMBO LIGHTING 1, 2, 3 AND 4 HEADS FLANGED AND TRIMLESS



Catalog Number Project Name



Description

A recessed LED multiple combo light featuring 1, 2, 3, or 4 LED luminaires, each producing 1200 lumens. Fully interchangeable optics makes it easy to change beam spreads in the field. Each individual LED module can be rotated 360° horizontally and 20° vertically for precise aiming. Streamlined rectangular profile fits into modern interiors. High-output LED arrays and high efficacy equal excellent performance and color quality. IC Rated: can be used in aeas where insulation is required.

DELIVERED LUMENS		WATTAGE		EFFICACY		
1200 Lumens/ head		15 watts		80 lumens/watts		
CCT	3000K, 4000K	VOLTAGE	120, 120-277	TRIM OPTION	Flanged, Trimless	
CRI	CRI > 90	BEAM ANGLE	15, 25 & 39 Deglee	FINISH	White, Black	
DIMMING	Triac, 0-10V Dimming	RATINGS	IC Rated, ETL, Title-24	WARRANTY		

COMPLETE FAMILY







LS26-COMB01

LS26-COMB02

LS26-COMBO3



LS26-COMBO4







ORDERING

LS26-COMBO1-15W-25D-3K-0-10-UNV-FT-W-WH

SERIES	WATTS	BEAM ANGLE	ССТ	DIM/VOLT	TRIM	HEAD COLOR	TRIM COLOR
LS26-COMB01 LS26-COMB02 LS26-COMB03 LS26-COMB04	15W	15D-15 Degree 25D-25 Degree 39D-39 Degree	3K-3000K 4K-4000K	TRIAC/UNV 0-10V/UNV	FT-Flanged Trim TL-Trimless	W- White B-Black	WH-White BK-Black

LS26-COMBO2

LED COMBO LIGHTING 1, 2, 3 AND 4 HEADS FLANGED AND TRIMLESS



Catalog Number **Project Name**

FULLY INTERCHANGEABLE, EASY TO SERVICE

EASY INSTALLATION

Field-changeable modular components let you remove and upgrade your light without replacing the junction box. The LED module and trim styles are completely interchangeable & easy to service and swap out. LED light engine and driver are replaceable, upgradeable, and can be accessed from above and below the ceiling.

MOUNTING FRAME & BRACKET

Pre-installed bar hangers can be shortened to position and lock housing at any point within the joist span. Bar hangers can fit onto T-Bar spline with additional slots and holes for special mounting, if necessar

FLANGED TRIM AND TRIMLESS OPTIONS

Available in 4 combinations of black and white. Trim option attaches to housing with secure clips for snug fit and zero light leakage. Trimless option is secured to housing with a safty cable.

HOUSING

Heavy-gauge steel and post-painted. Adjusts d accommodate a variety of ceiling heights. Interior painted matte black for glærfree illumination, maximum heat dissipation, and pro internal reflection. Die-cast aluminum luminaire heads dissipate heat.

ADJUSTABILITY

Amp swivel allows for precise rotation and aiming. Angle can then be looked into position without the use of bols. Each individual LED module can be rotated 360° horizontally and 20° vertically for precise aiming.

OPTICS AND REFLECTOR

A multi-segmented eflector provides precise beam contol and field-chang able optics in Spot, Narow, and Flood. Each luminaie head can sewe different functions of illumination.

HEAD/TRIM COLOR OPTIONS



W-WH-WHITE-WHITE



B-BK-BLACK-BLACK



B-WH-BLACK-WHITE



W-BK-WHITE-BLACK

TRIM OPTIONS



FT-FLANGED TRIM



TL-TRIMLESS

LS26-COMBO2


LED COMBO LIGHTING 1, 2, 3 AND 4 HEADS FLANGED AND TRIMLESS

SP)T₂₆


Catalog Number


Project Name

DIMENSIONS



HEAD DIMENSIONS








.....

HOUSING DIMENSIONS













FLANGED TRIM DIMENSIONS









TRIMLESS DIMENSIONS

