LS26-COMBO4

LED COMBO LIGHTING 1, 2, 3 AND 4 HEADS FLANGED AND TRIMLESS

#### **Catalog Number**



Project Name



#### Description

A recessed LED multiple combo light featuring 1, 2, 3, or 4 LED luminaires, each producing 1200 lumens. Fully interchangeable optics makes it easy to change beam spreads in the field. Each individual LED module can be rotated 360° horizontally and 20° vertically for precise aiming. Streamlined rectangular profile fits into modern interiors. High-output LED arrays and high efficacy equal excellent performance and color quality. IC Rated: can be used in areas where insulation is required.

DELIVERED LUMENS		WATTAGE		EFFICACY		
1200 Lumens/ head		15 watts		80 lumens/watts		
ССТ	3000К, 4000К	VOLTAGE	120, 120-277	TRIM OPTION	Flanged, Trimless	
CRI	CRI > 90	BEAM ANGLE	15, 25 & 39 Degree	FINISH	White, Black	
DIMMING	Triac, 0-10V Dimming	RATINGS	IC Rated, ETL, Title-24	WARRANTY		

## **COMPLETE FAMILY**





LS26-COMB04



## ORDERING

# LS26-COMB01-15W-25D-3K-0-10-UNV-FT-W-WH

SERIES	WATTS	BEAM ANGLE	ССТ	DIM/VOLT	TRIM	HEAD COLOR	TRIM COLOR
LS26-COMBO1 LS26-COMBO2 LS26-COMBO3 LS26-COMBO4	15W	15D-15 Degree 25D-25 Degree 39D-39 Degree	3K-3000K 4K-4000K	TRIAC/UNV 0-10V/UNV	FT-Flanged Trim TL-Trimless	W- White B-Black	WH-White BK-Black





#### Project Name

# FULLY INTERCHANGEABLE, EASY TO SERVICE

#### EASY INSTALLATION

Field-changeable modular components let you remove and upgrade your light without replacing the junction box. The LED module and trim styles are completely interchangeable & easy to service and swap out. LED light engine and driver are replaceable, upgradeable, and can be accessed from above and below the ceiling.

# **MOUNTING FRAME & BRACKET**

Pre-installed bar hangers can be shortened to position and lock housing at any point within the joist span. Bar hangers can fit onto T-Bar spline with additional slots and holes for special mounting, if necessary.

## FLANGED TRIM AND TRIMLESS OPTIONS

Available in 4 combinations of black and white. Trim option attaches to housing with secure clips for snug fit and zero light leakage. Trimless option is secured to housing with a safety cable.

## HOUSING

Heavy-gauge steel and post-painted. Adjusts to accommodate a variety of ceiling heights. Interior painted matte black for glare-free illumination, maximum heat dissipation, and zero internal reflection. Die-cast aluminum luminaire heads dissipate heat.

### ADJUSTABILITY

Amp swivel allows for precise rotation and aiming. Angle can then be locked into position without the use of tools. Each individual LED module can be rotated 360° horizontally and 20° vertically for precise aiming.

### **OPTICS AND REFLECTOR**

A multi-segmented reflector provides precise beam control and field-changeable optics in Spot, Narrow, and Flood. Each luminaire head can serve different functions of illumination.

# **HEAD/TRIM COLOR OPTIONS**



W-WH-WHITE-WHITE



B-BK-BLACK-BLACK



**B-WH**-BLACK-WHITE



W-BK-WHITE-BLACK

## **TRIM OPTIONS**



FT-FLANGED TRIM



TL-TRIMLESS



# LS26-COMBO4

LED COMBO LIGHTING 1, 2, 3 AND 4 HEADS FLANGED AND TRIMLESS

#### **Catalog Number**

**Project Name** 





**HEAD DIMENSIONS** 



