



Project _____ Catalog # _____

LSRE-T35RA5CT

3.5" LED Adjustable Gimbal Retrofit Downlight

LUMENS: 760-830lm

COLOR TEMPERATURE: Selectable 5CCT

APERTURE: Round Adjustable

Description 3.5" LED adjustable gimbal retrofit is compatible with most 3.5" standard recessed new construction and remodel housings.

FEATURES

- 760-830lm / 9W
- Selectable CCT: 2700K, 3000K, 3500K, 4000K, 5000K @ 90+ CRI
- Black or White finishes
- Adjustable Gimbal can be rotated 25° vertically and 358° horizontally
- Die-cast aluminum heatsink dissipates heat from LED board
- 3 Tension clips pre-installed on unit for easy installation
- Dimming down to 10% with most dimmers
- Certified to the high efficacy requirements of California JA8 Title 24
- cULus listed
- ENERGY STAR Certified
- RoHS compliances
- Tested in accordance with IESNA LM79 & LM80




PRODUCT IMAGES & DIMENSIONS



LSRE-T35RA5CTBK
3.5" Adjustable Gimbal,
Black finish



LSRE-T35RA5CTWH
3.5" Adjustable Gimbal,
White finish



SPECIFICATIONS

Catalog Number	Size	Type/Finish	Selectable CCT / Lumen	CRI	Certificated
LSRE-T35RA5CTBK	3.5"	Adjustable Gimbal/Black	27K/760lm; 30K/780lm; 35K/800lm; 40K/820lm; 50K/830lm	90+	cULus
LSRE-T35RA5CTWH	3.5"	Adjustable Gimbal//White	27K/760lm; 30K/780lm; 35K/800lm; 40K/820lm; 50K/830lm	90+	cULus