



LSRL-4WT5CCT

4" Wattage Tuning & CCT Selectable LED Retrofit Downlight

LUMENS: 500/700/850lm

COLOR TEMPERATURE: Selectable 5CCT

APERTURE: Round

Wattage & CCT Switch



Description 4" Wattage tuning and CCT selectable Retrofit series include two tunable switches; Selectable Lumens allows the end user to determine the wattage input and Selectable CCT allows for changing the color temperature appearance. Spun aluminum construction provides clean sharp edges and is suitable for use with most 4" recessed housings. Deep regressed optics and round aperture deliver even and glare-free illumination.

FEATURES

- Wattage tuning: 500lm/4W; 700lm/10W; 850lm/12W
- Selectable CCT: 2700K, 3000K, 3500K, 4000K, 5000K @ 90+CRI
- Baffle or Smooth reflector
- Includes medium base socket adapter for easy retrofitting in 4" recessed housings
- Certified to the high efficacy requirements of California JA8 Title 24
- cETLus listed
- ENERGY STAR Certified




PRODUCT IMAGES & DIMENSIONS



LSRL-4WT5CCTSBL
4" Smooth, Black finish




LSRL-4WT5CCTSWH
4" Smooth, White finish



LSRL-4WT5CCTBBL
4" Baffle, Black finish



LSRL-4WT5CCTBWH
4" Baffle, White finish



SPECIFICATIONS

Catalog Number	Size	Type/Finish	Selectable Lumen/Wattage	Selectable CCT	CRI	Certified
LSRL-4WT5CCTSBL	4"	Smooth/Black	500lm/4W; 700lm/10W; 850lm/12W	27K/30K/35K/40K/50K	90+	cETLus
LSRL-4WT5CCTSWH	4"	Smooth/White	500lm/4W; 700lm/10W; 850lm/12W	27K/30K/35K/40K/50K	90+	cETLus
LSRL-4WT5CCTBBL	4"	Baffle/Black	500lm/4W; 700lm/10W; 850lm/12W	27K/30K/35K/40K/50K	90+	cETLus
LSRL-4WT5CCTBWH	4"	Baffle/White	500lm/4W; 700lm/10W; 850lm/12W	27K/30K/35K/40K/50K	90+	cETLus